

Alloy langlenket kjetting G64 galvanisert



QR Code

Product Image



Varenr. varmgalv.	Varenr. termogalv.	Produkt ID	Prøvelast		MBL		Dimensjoner (mm)			Vekt (kg/m)
			tonn	kN	tonn	kN	D	L	B	
115110	215110	11x66	5.6	54.9	12.4	122	11	66	18	2.1
115130	215130	13x81	7.8	76.5	17.3	170	13	81	22	2.7
115161	215161	16x100	11.8	116	26.2	257	16	100	26	4.4
115192	215192	19x100	16.7	163	37.0	363	19	100	32	6.5
115222	215222	22x120	22.3	219	49.6	487	22	120	35	8.5
-	215250	25x140	28.8	283	64.0	628	25	140	41	11.0
-	215280	28x150	36.1	355	80.3	788	28	150	45	14.0
-	215320	32x170	47.2	463	104.9	1029	32	170	47	19.0
-	215380	38x185	68.4	671	152.1	1492	38	185	57	26.5

Alloy langlenket kjetting G64 galvanisert



Korrosjonsbeskyttet kjetting til fiskeri og akvakultur, tilgjengelig med termogalvanisering og tradisjonell varmgalvanisering. Sertifisert iht. NS9415:2021 og NYTEK23, til bruk i flytende oppdrettsanlegg.